

## Statement of Verification

BREG EN EPD No.: 000587

Issue 01

This is to verify that the  
**Environmental Product Declaration**  
provided by:  
**Amtico International**



is in accordance with the requirements of:  
**EN 15804:2012+A2:2019**  
and  
**BRE Global Scheme Document SD207**

This declaration is for:  
**1m2 Amtico Signature (3.15kg/m2)**

### Company Address

Amtico International  
Kingfield Road,  
Coventry  
UK  
CV6 5AA



Laura Critien  
Operator

30 May 2024  
Date of this Issue

30 May 2024  
Date of First Issue

29 May 2029  
Expiry Date



This Statement of Verification is issued subject to terms and conditions (for details visit [www.greenbooklive.com/terms](http://www.greenbooklive.com/terms).  
To check the validity of this statement of verification please, visit [www.greenbooklive.com/check](http://www.greenbooklive.com/check) or contact us.  
BRE Global Ltd., Garston, Watford WD25 9XX.  
T: +44 (0)333 321 8811 F: +44 (0)1923 664603 E: [Enquiries@breglobal.com](mailto:Enquiries@breglobal.com)



## Environmental Product Declaration

EPD Number: **000587**

### General Information

EPD Programme Operator	Applicable Product Category Rules
BRE Global Watford, Herts WD25 9XX United Kingdom	BRE 2023 Product Category Rules (PN 514 Rev 3.1) for Type III environmental product declaration of construction products to EN 15804:2012+A2:2019.
Commissioner of LCA study	LCA consultant/Tool
Amtico International Kingfield Road, Coventry UK CV6 5AA	John Baggaley/BRE LINA A2
Declared/Functional Unit	Applicability/Coverage
1m <sup>2</sup> Amtico Signature (3.15kg/m <sup>2</sup> )	Product Specific.
EPD Type	Background database
Cradle to Gate with module C and D and options	Ecoinvent v3.8 (2021)
Demonstration of Verification	
CEN standard EN 15804 serves as the core PCR <sup>a</sup>	
Independent verification of the declaration and data according to EN ISO 14025:2010 <input type="checkbox"/> Internal <input checked="" type="checkbox"/> External	
(Where appropriate <sup>b</sup> )Third party verifier: Roger Connick	
a: Product category rules b: Optional for business-to-business communication; mandatory for business-to-consumer communication (see EN ISO 14025:2010, 9.4)	
Comparability	
Environmental product declarations from different programmes may not be comparable if not compliant with EN 15804:2012+A2:2019. Comparability is further dependent on the specific product category rules, system boundaries and allocations, and background data sources. See Clause 5.3 of EN 15804:2012+A2:2019 for further guidance	

## Information modules covered

Product			Construction		Use stage							End-of-life				Benefits and loads beyond the system boundary
					Related to the building fabric					Related to the building						
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Raw materials supply	Transport	Manufacturing	Transport to site	Construction – Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, Recovery and/or Recycling potential
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Note: Ticks indicate the Information Modules declared.

## Manufacturing site(s)

Amtico International  
 Kingfield Road  
 Coventry  
 United Kingdom  
 CV6 5AA

## Construction Product:

### Product Description

Amtico Signature is a premium LVT collection, consisting of a range of wood, stone and abstract designs, available in a range of finishes and sizes, including unique laying patterns.

Amtico Signature products have a total thickness of 2.5mm with a 1mm wear layer, providing a usage classification (EN ISO 10582) of

1. 23 Heavy Domestic
2. 34 Very Heavy Commercial
3. 43 Heavy Light Industrial

The Signature Collection comes with a lifetime wear out warranty for residential installation and 20 years for commercial use.

Signature is manufactured from ortho-phthalate free plasticisers, contains up to 14% recycled pre-consumer content and also includes an antimicrobial additive, for enhanced hygiene and protection from bacteria and viruses such as MRSA, E. coli and SARS-CoV-2.

Signature is a low VOC product, certified to Eurofins Indoor Air Comfort Gold and Finnish RTS M1.

## Technical Information

Property	Value, Unit
Usage Classification (EN ISO 10874)	23,34,43
Manufacturing Standard (EN ISO 10582)	Conforms
Wear Layer Thickness (EN ISO 24340)	1.0mm
Total Thickness (EN ISO 24346)	2.5mm
Weight (EN ISO 23997)	3.15kg/m <sup>2</sup>
Flammability /Smoke Emissions (EN 13501-1)	B <sub>f1</sub> s1
Slip Resistance (EN13893)	Class DS
Electrostatic Propensity EN 1815	≤ 2kV
Thermal Resistance EN 12667	0.014 m <sup>2</sup> K/W
VOC Emissions Eurofins Indoor Air Comfort Gold	IACG-352-01-12-2022B
Full TDS can be found at <a href="http://www.amtico.com">www.amtico.com</a>	

### Construction | Multiple Performance System

Total thickness of product: 2.5mm\*

**A. Quantum Guard Elite**

Amtico's patented urethane formula provides superior durability and resistance against abrasions and stains. The reinforced low gloss finish is highly realistic

**B. Superior 1mm wear layer**

Toughened upper layer, giving excellent impact resistance and high clarity, allowing the product designs to shine through.

**C. Design layers**

High resolution print layers over deeply coloured base layers create the distinctive Wood, Stone and Abstract designs that set Amtico apart.


**D. Backing layer**

The foundation of the product which provides long lasting stability. Contains up to 30% recycled pre-consumer content.

**E. Acoustic backing layer (optional)**

Reduces the impact sound by up to 18dB and provides an extra level of comfort underfoot.

\*3.5mm with optional Acoustic backing.



## Main Product Contents

Material/Chemical Input	%
Polyurethane Lacquer	<0.5
Polyvinyl Chloride	62
Plasticisers	17
Print Film	2
Calcium Carbonate	16
Stabiliser, Process Aids & Pigments	<2.5

## Manufacturing Process


The product is constructed by the thermal lamination of the wear layer, print film and backing plies. The wear layer and backing plies are all manufactured as follows

1. Required ply raw materials are initially blended
2. The ply blend is then heated and calendered on a mill to produce a ply of the required thickness.
3. The plies required to form the end product, along with the print film, are thermally laminated together under pressure, to form the final product.
4. The product is then coated with polyurethane, before being cut to size, boxed and dispatched to the customer.
5. Cutting waste is reground on-site and reused in the production of further backing plies.

Process flow diagram

**Raw Material Delivery**  
 Amtico Production Process Flow Diagram

Q8F-TEC.0034



**Amtico International Head Office**  
 Kingfield Road, Coventry  
 CV6 5AA, UK

+44 (0) 24 7686 1400  
 info@amtico.com  
 amtico.com



**Construction Installation**

Amtico Signature should be bonded with a suitably low emissions adhesive to an appropriately prepared subfloor as detailed in BS8302.

Details for Amtico Signature installation can be found at [www.amtico.com](http://www.amtico.com)

**Use Information**

The Amtico Signature manufacturing site is certificated to ISO 9001, ISO 14001 and ISO 45001.

Amtico Signature adheres to the emission requirements of Indoor Air Comfort Gold, German AgBB/DIBt, Belgium, and is rated as A+ in the French "Emissions dans l'air interieur" scheme.

**End of Life**

At the end of the product's life, the flooring is mechanically removed from the subfloor and disposed of by landfill, incineration/energy recovery or recycling. It is assumed that no energy required to remove the floor.

It is assumed that 87% of the product will go to landfill, 12% to incineration/energy recovery schemes and 1% to recycling. The distance travelled from the demolition site to a disposal site will be no more than 200km.

## Life Cycle Assessment Calculation Rules

### Declared / Functional unit description

1m<sup>2</sup> Amtico Signature (3.15kg/m<sup>2</sup>)

### System boundary

This is a cradle-to-gate with module C and D and options LCA study that follows the modular design defined in EN15804:2012+A2:2019 and BRE 2023 Product Category Rules (PN 514 Rev 3.1) and includes the processes covered in the manufacturing site and product stage A1 to A3, A4, A5, B2, C1-C4 and D.

### Data sources, quality and allocation

Specific primary data derived from Amtico's production process in the Coventry factory, have been modelled using the BRE LINA A2 software and the Ecoinvent v3.8 (2021) database. In accordance with the requirements of EN15804:2012+A2:2019, the most current available data has been used. The manufacturer-specific data from Amtico covers a period of one year (01/01/2021 – 31/12/2021). Secondary data has been obtained for all other upstream and downstream processes that are beyond the control of the manufacturer (i.e. raw material production) from the Ecoinvent v3.8 (2021) database. All Ecoinvent v3.8 (2021) datasets are complete within the context used and conform to the system boundary and the criteria for the exclusion of inputs and outputs, according to the requirements specified in EN15804:2012+A2:2019.

Amtico manufactures other LVT products at its production site, in addition to the product covered by this EPD. Calculations were performed to enable allocation of total site energy use, water and waste to the Amtico Signature product. Allocation procedures were by mass allocation and are according to EN 15804 and are based on the ISO14044 guidance. All the input and output materials such as packaging, transportation, energy, water use and wastes are included. Only exceptions are outputs to air, water or soil as these are not measured at the site.

Products manufactured in Coventry are then distributed in the UK, across Europe, Scandinavia, the Middle and Far East. The average distance transported for each geographical market was calculated by multiplying the distance travelled by the percentage sales volume by square meter. Regions where sales were less than 1% were not considered.

The electricity supply was determined by the electricity supplier's meters. The assumed electricity generation GWP was 0.312 kg CO<sub>2</sub> eq./kWh (Electricity, GB).

Natural gas is used for heat generation and steam production. The assumed GWP was 0.232 kg CO<sub>2</sub> eq./kWh (Natural gas, at industrial furnace, GB).

Wastewater to sewer was determined by a water meter.

Module C4 end of life assumes that 1% of the PVC flooring is recycled, 12% is used in energy recovery/incineration, with the remainder going to landfill. This ratio is based on a study performed by BRE.

Quality Level	Geographical representativeness	Technical representativeness	Time representativeness
Very Good	Data from area under study.	Data from processes and products under study. Same state of technology applied as defined in goal and scope (i.e. identical technology).	There is less than 5 years between the Ecoinvent v3.8 (2021) LCI reference year, and the time period for which the LCA was undertaken.

Specific UK datasets have been selected from the Ecoinvent v3.8 (2021) LCI for this LCA. The quality level of geographical and technical representativeness is therefore Very Good. The quality level of time representativeness is Very Good as the background LCI datasets are based on Ecoinvent v3.8 (2021) which was compiled in 2021. Therefore, there is less than 5 years between the Ecoinvent v3.8 (2021) LCI reference year and the time period for which the LCA was undertaken.

### Cut-off criteria

All stages of the manufacturing process have been included. Transport distances to site were not calculated for Sales Business Units with <1% of product sales. The product life was based on the residential 35 years warranty. All inputs or outputs have been included and all raw materials, packaging and transport, energy, water use and wastes, are included, except for direct emissions to air, water and soil, which are not measured. Upstream extraction and/or processing of inputs are included within the use of the background datasets within LINA.



## LCA Results

(MND = module not declared; MNR = module not relevant; INA = indicator not assessed; AGG = aggregated)

Parameters describing environmental impacts			GWP-total	GWP-fossil	GWP-biogenic	GWP-luluc	ODP	AP	EP-freshwater
			kg CO <sub>2</sub> eq	kg CO <sub>2</sub> eq	kg CO <sub>2</sub> eq	kg CO <sub>2</sub> eq	kg CFC11 eq	mol H <sup>+</sup> eq	kg (PO <sub>4</sub> ) <sup>3-</sup> eq
Product stage	Raw material supply	A1	6.63E+00	5.40E+00	5.88E-01	6.32E-01	1.00E-05	2.56E-02	4.81E-03
	Transport	A2	1.87E-01	1.87E-01	1.17E-04	8.88E-05	4.22E-08	2.41E-03	9.96E-06
	Manufacturing	A3	1.55E+00	1.78E+00	-2.39E-01	2.63E-03	1.38E-07	4.69E-03	2.67E-04
	Total (of product stage)	A1-3	8.36E+00	7.37E+00	3.49E-01	6.35E-01	1.02E-05	3.27E-02	5.08E-03
Construction process stage	Transport	A4	4.98E-01	4.97E-01	1.09E-03	3.09E-04	1.05E-07	2.75E-03	7.15E-05
	Construction	A5	1.21E+00	7.79E-01	3.47E-01	8.63E-02	3.89E-07	4.11E-03	7.06E-04
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	1.27E+00	1.22E+00	4.76E-02	1.12E-03	1.21E-07	9.03E-03	5.25E-04
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>									
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	1.05E-01	1.05E-01	8.93E-05	4.11E-05	2.42E-08	4.25E-04	6.74E-06
	Waste processing	C3	8.10E-01	8.08E-01	1.70E-03	1.18E-04	2.59E-08	6.26E-04	3.64E-05
	Disposal	C4	2.31E-01	2.31E-01	2.90E-04	3.03E-05	8.79E-09	2.52E-04	4.22E-06
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-2.95E-01	-2.92E-01	-3.18E-03	-3.02E-04	-5.08E-08	-1.61E-03	-1.40E-04

GWP-total = Global warming potential, total;  
 GWP-fossil = Global warming potential, fossil;  
 GWP-biogenic = Global warming potential, biogenic;  
 GWP-luluc = Global warming potential, land use and land use change;

ODP = Depletion potential of the stratospheric ozone layer;  
 AP = Acidification potential, accumulated exceedance; and  
 EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment

## LCA Results (continued)

Parameters describing environmental impacts			EP-marine	EP-terrestrial	POCP	ADP-mineral & metals	ADP-fossil	WDP	PM
			kg N eq	mol N eq	kg NMVOC eq	kg Sb eq	MJ, net calorific value	m <sup>3</sup> world eq deprived	disease incidence
Product stage	Raw material supply	A1	6.39E-03	4.42E-02	1.61E-02	8.99E-05	1.37E+02	4.83E+00	2.01E-07
	Transport	A2	6.25E-04	6.91E-03	1.90E-03	3.85E-07	2.75E+00	1.14E-02	1.67E-08
	Manufacturing	A3	1.43E-03	1.32E-02	3.39E-03	4.40E-06	4.01E+01	3.61E-01	3.86E-08
	Total (of product stage)	A1-3	8.45E-03	6.43E-02	2.14E-02	9.46E-05	1.80E+02	5.20E+00	2.56E-07
Construction process stage	Transport	A4	8.31E-04	9.13E-03	2.96E-03	7.15E-06	7.37E+00	5.30E-02	5.32E-08
	Construction	A5	1.30E-03	8.60E-03	2.89E-03	1.13E-05	1.82E+01	9.37E-01	4.11E-08
Use stage	Use	B1	MND	MND	MND	MND	MND	MND	MND
	Maintenance	B2	5.20E-03	1.60E-02	5.22E-03	1.74E-05	3.55E+01	1.55E+00	1.05E-07
	Repair	B3	MND	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>									
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	1.28E-04	1.40E-03	4.28E-04	3.64E-07	1.58E+00	7.12E-03	9.04E-09
	Waste processing	C3	1.85E-04	1.68E-03	4.72E-04	9.14E-07	1.35E+00	1.51E+00	5.40E-09
	Disposal	C4	1.08E-03	9.22E-04	3.14E-04	9.62E-08	6.84E-01	3.06E-02	4.98E-09
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-2.52E-04	-2.51E-03	-7.36E-04	-1.29E-06	-5.05E+00	-1.34E-01	-1.20E-08

EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment;  
 EP-terrestrial = Eutrophication potential, accumulated exceedance;  
 POCP = Formation potential of tropospheric ozone;  
 ADP-mineral&metals = Abiotic depletion potential for non-fossil resources;

ADP-fossil = Depletion potential of the stratospheric ozone layer;  
 WDP = Water (user) deprivation potential, deprivation-weighted water consumption; and  
 PM = Particulate matter.

## LCA Results (continued)

Parameters describing environmental impacts			IRP	ETP-fw	HTP-c	HTP-nc	SQP
			kBq U <sup>235</sup> eq	CTUe	CTUh	CTUh	dimensionless
Product stage	Raw material supply	A1	7.35E-01	1.10E+02	5.48E-09	1.22E-07	4.43E+01
	Transport	A2	1.35E-02	2.02E+00	7.86E-11	2.00E-09	2.34E+00
	Manufacturing	A3	1.03E+00	1.91E+01	7.73E-10	1.17E-08	3.85E+01
	Total (of product stage)	A1-3	1.78E+00	1.31E+02	6.33E-09	1.36E-07	8.51E+01
Construction process stage	Transport	A4	4.63E-02	7.33E+00	7.75E-10	9.35E-09	3.61E+00
	Construction	A5	1.21E-01	2.03E+01	6.02E-10	1.50E-08	8.67E+00
Use stage	Use	B1	MND	MND	MND	MND	MND
	Maintenance	B2	7.26E-02	1.01E+02	3.35E-09	6.36E-08	5.56E+00
	Repair	B3	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>							
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	8.14E-03	1.24E+00	4.00E-11	1.30E-09	1.09E+00
	Waste processing	C3	8.98E-03	4.45E+01	1.75E-10	1.25E-08	7.89E-01
	Disposal	C4	3.23E-03	1.06E+01	2.33E-11	2.05E-09	1.62E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-6.02E-02	-4.62E+00	-9.98E-11	-2.93E-09	-1.23E+00

IRP = Potential human exposure efficiency relative to U235;  
 ETP-fw = Potential comparative toxic unit for ecosystems;  
 HTP-c = Potential comparative toxic unit for humans;

HTP-nc = Potential comparative toxic unit for humans; and  
 SQP = Potential soil quality index.

## LCA Results (continued)

			Parameters describing resource use, primary energy					
			PERE	PERM	PERT	PENRE	PENRM	PENRT
			MJ	MJ	MJ	MJ	MJ	MJ
Product stage	Raw material supply	A1	8.30E+00	4.35E+00	1.27E+01	8.08E+01	5.62E+01	1.37E+02
	Transport	A2	3.06E-02	0.00E+00	3.06E-02	2.69E+00	0.00E+00	2.69E+00
	Manufacturing	A3	5.68E+00	4.80E+00	1.05E+01	3.52E+01	5.05E+00	4.02E+01
	Total (of product stage)	A1-3	1.40E+01	9.15E+00	2.32E+01	1.19E+02	6.12E+01	1.80E+02
Construction process stage	Transport	A4	1.97E-01	0.00E+00	1.97E-01	7.25E+00	0.00E+00	7.25E+00
	Construction	A5	-1.86E+00	5.08E+00	3.23E+00	7.78E+00	8.56E+00	1.63E+01
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	1.59E+00	0.00E+00	1.59E+00	1.30E+01	2.09E+01	3.39E+01
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>								
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	2.23E-02	0.00E+00	2.23E-02	1.55E+00	0.00E+00	1.55E+00
	Waste processing	C3	1.15E-01	0.00E+00	1.15E-01	-8.23E+00	9.47E+00	1.24E+00
	Disposal	C4	1.22E-02	0.00E+00	1.22E-02	-5.83E+01	5.89E+01	6.72E-01
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-4.38E-01	0.00E+00	-4.38E-01	-2.43E+00	6.69E-01	-1.76E+00

PERE = Use of renewable primary energy excluding renewable primary energy used as raw materials;  
 PERM = Use of renewable primary energy resources used as raw materials;  
 PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;  
 PENRM = Use of non-renewable primary energy resources used as raw materials;  
 PENRT = Total use of non-renewable primary energy resource

## LCA Results (continued)

Parameters describing resource use, secondary materials and fuels, use of water						
			SM	RSF	NRSF	FW
			kg	MJ net calorific value	MJ net calorific value	m <sup>3</sup>
Product stage	Raw material supply	A1	0.00E+00	0.00E+00	0.00E+00	1.15E-01
	Transport	A2	0.00E+00	0.00E+00	0.00E+00	2.81E-04
	Manufacturing	A3	1.12E-02	3.63E-07	0.00E+00	8.98E-03
	Total (of product stage)	A1-3	1.12E-02	3.63E-07	0.00E+00	1.24E-01
Construction process stage	Transport	A4	0.00E+00	0.00E+00	0.00E+00	1.32E-03
	Construction	A5	3.78E-04	1.09E-08	0.00E+00	2.21E-02
Use stage	Use	B1	MND	MND	MND	MND
	Maintenance	B2	3.95E-03	0.00E+00	0.00E+00	3.66E-02
	Repair	B3	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>						
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	0.00E+00	0.00E+00	0.00E+00	1.76E-04
	Waste processing	C3	0.00E+00	0.00E+00	0.00E+00	3.52E-02
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	7.20E-04
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	-3.30E-03

SM = Use of secondary material;  
RSF = Use of renewable secondary fuels;

NRSF = Use of non-renewable secondary fuels;  
FW = Net use of fresh water

## LCA Results (continued)

Other environmental information describing waste categories			HWD	NHWD	RWD
			kg	kg	kg
Product stage	Raw material supply	A1	3.67E-01	8.30E+00	2.44E-04
	Transport	A2	3.10E-03	4.49E-02	1.27E+01
	Manufacturing	A3	7.28E-02	1.16E+00	2.83E-04
	Total (of product stage)	A1-3	4.43E-01	9.50E+00	1.27E+01
Construction process stage	Transport	A4	1.51E-02	3.09E-01	4.50E+01
	Construction	A5	5.54E-02	1.26E+00	3.81E-01
Use stage	Use	B1	MND	MND	MND
	Maintenance	B2	9.13E-02	1.61E+00	2.37E-01
	Repair	B3	MND	MND	MND
	Replacement	B4	MND	MND	MND
	Refurbishment	B5	MND	MND	MND
	Operational energy use	B6	MND	MND	MND
	Operational water use	B7	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>					
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	1.75E-03	3.10E-02	1.07E-05
	Waste processing	C3	2.09E-01	5.15E-01	6.16E-06
	Disposal	C4	1.36E-03	2.77E+00	4.06E-06
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	-8.40E-03	-6.39E-01	-1.46E-05

HWD = Hazardous waste disposed;  
 NHWD = Non-hazardous waste disposed;  
 RWD = Radioactive waste disposed

## LCA Results (continued)

Other environmental information describing output flows – at end of life								
			CRU	MFR	MER	EE	Biogenic carbon (product)	Biogenic carbon (packaging)
			kg	kg	kg	MJ per energy carrier	kg C	kg C
Product stage	Raw material supply	A1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	-8.71E-02	0.00E+00
	Transport	A2	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Manufacturing	A3	0.00E+00	1.60E-01	2.34E-08	7.16E-04	7.86E-03	-5.39E-02
	Total (of product stage)	A1-3	0.00E+00	1.60E-01	2.34E-08	7.16E-04	-7.92E-02	-5.39E-02
Construction process stage	Transport	A4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Construction	A5	0.00E+00	3.26E-01	6.03E-09	2.15E-05	1.07E-02	7.02E-02
Use stage	Use	B1	MND	MND	MND	MND	MND	MND
	Maintenance	B2	0.00E+00	5.65E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Repair	B3	MND	MND	MND	MND	MND	MND
	Replacement	B4	MND	MND	MND	MND	MND	MND
	Refurbishment	B5	MND	MND	MND	MND	MND	MND
	Operational energy use	B6	MND	MND	MND	MND	MND	MND
	Operational water use	B7	MND	MND	MND	MND	MND	MND
<b>87% Landfill, 12% Incineration/Energy Recovery, 1% Recycled</b>								
End of life	Deconstruction, demolition	C1	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Transport	C2	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	Waste processing	C3	0.00E+00	3.15E-02	3.78E-01	0.00E+00	0.00E+00	0.00E+00
	Disposal	C4	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Potential benefits and loads beyond the system boundaries	Reuse, recovery, recycling potential	D	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00

CRU = Components for reuse;  
MFR = Materials for recycling

MER = Materials for energy recovery;  
EE = Exported Energy

## Scenarios and additional technical information

Scenarios and additional technical information			
Scenario	Parameter	Units	Results
A4 – Transport to the building site	<p>Products manufactured at Coventry are disturbed in the UK, across Europe, Scandinavia, the Middle and Far East. The average distance transported for each geographical market was calculated by multiplying the distance travelled by the percentage sales volume by square meter. Regions where sales were less than 1% of the total sales were not considered.</p> <p>The sales volumes were those in 2021. The transportation data is taken from Ecoinvent v3.8 (2021) datasets.</p>		
	<b>UK Direct Delivery:</b>	Diesel / Van	0.32l/km
	Distance:	km	163
	Capacity utilisation (incl. empty returns)	%	61
	Bulk density of transported products	kg/m <sup>3</sup>	1260
	<b>Worldwide: Road</b>	Diesel / 16-32 tonne Lorry	0.032l/km
	Distance:	km	384
	Capacity utilisation (incl. empty returns)	%	61
	Bulk density of transported products	kg/m <sup>3</sup>	1260
	<b>Worldwide: Sea</b>	Marine Bunker Oil / Container Ship	0.21tonnes/km
	Distance:	km	494
	Capacity utilisation (incl. empty returns)	%	65
	Bulk density of transported productskg/m3	kg/m <sup>3</sup>	1260
A5 – Installation in the building	<p>Amtico Signature should be bonded with a suitable, low emissions adhesive to an appropriately prepared subfloor as detailed in BS8302. Full details on installation can be found at <a href="http://www.amtico.com">www.amtico.com</a></p>		
	Installation Wastage Rate	%	3
	Post installation Cleaning	l/m <sup>2</sup>	0.02
	Ancillary Materials	Mass per unit area of product installed kg/m <sup>2</sup>	0.287
	Material Waste	Installation off cuts mass per unit area of product installed kg/m <sup>2</sup>	0.0945
	Cardboard Packaging	Mass per unit area of product installed kg/m <sup>2</sup>	0.158



Scenarios and additional technical information			
Scenario	Parameter	Units	Results
	Wood Packaging	Mass per unit area of product installed kg/m <sup>2</sup>	0.209
	Shrink Wrap	Mass per unit area of product installed kg/m <sup>2</sup>	0.007
B2 – Maintenance	<p>The required recommended cleaning and maintenance regime is dependent on the place of installation and the foot traffic over the floor. High traffic areas will generally require more cleaning and maintenance than low traffic situations.</p> <p>Dry cleaning may be performed with a dust mop or with a vacuum cleaner. Wet cleaning can be performed with a mop, detergent and water. Power cleaning is also a possibility with scrubber driers etc.</p> <p>The calculations are assumed for 1m<sup>2</sup> per year</p>		
	52 Wet Cleans per year (Water use)	l/yr./m <sup>2</sup>	3.224
	Detergent usage	kg/yr./m <sup>2</sup>	0.0416
Reference service life	<p>Amtico International guarantees that in the event of the Amtico Signature flooring supplied to the original purchaser under their agreement, requiring replacement due to 'Wear-out' from normal foot traffic within thirty-five years from the date of purchase, the floor will be repaired or replaced with the same or similar material free of charge. 'Wear-out' means the removal of the pattern and colour from the Amtico Signature floor caused by the removal of the protective wear layer. Reference service life used in LCA was the residential warranty.</p>		
	Residential Product Warranty.	Years	35
C1 to C4 End of life,	<p>Data for post-consumer end of life for PVC flooring scenarios is limited. BRE BREEAM PEP scheme (2008) assumed 87% went to landfill, 12% for incineration/energy recovery and 1% was recycled. An Axion report "Post-Zero Avoidable Waste in Flooring-Towards a Circular Economy", published February 2022, also has a figure of 1%. The 87:12:1 ratio was used in this study.</p>		
C1 Deconstruction	At the product's end of life that the product is manually mechanically removed from the sub-floor. No ancillary materials, energy or water was required for the process.	kg/m <sup>2</sup>	3.15
C2 Transport	<p>It is assumed that 87% of the dismantled floor goes to land fill, 12% is incinerated for energy recovery and 1% is recycled. The disposal sites are within 200km of the demolition site</p>		
	Disposal from demolition site to landfill	km	174
	Disposal from demolition site to incinerator/energy recovery plant	km	24
	Disposal from demolition site to recycling plant	km	2
C3 Waste Processing	<p>Minimal waste processing was considered necessary with no further ancillary materials, energy or water required.</p>		
	1% is recycled	kg/m <sup>2</sup>	0.0315
	12% is incinerated /energy recovery	kg/m <sup>2</sup>	0.378
C4 Disposal	87% of the material is assumed to go to landfill	kg/m <sup>2</sup>	2.7405


### Scenarios and additional technical information

Scenario	Parameter	Units	Results
Module D	BRE BREEAM PEP scheme used a recycling figure of 1% in its calculations. (2008). An Axion report "Post-Zero Avoidable Waste in Flooring-Towards a Circular Economy", published February 2022, also has a figure of 1%. The pre-existing recycled content in the raw material of 1.2% has been excluded from Module D. So only 98.8% of the 0.0315kg to recycling in C3 can be claimed for benefits.	Kg/m <sup>2</sup>	0.0311
	Data for post-consumer recycling rates for vinyl flooring is limited. BRE BREEAM PEP scheme used an energy recovery figure of 12% in its calculations. (2008)	Kg/m <sup>2</sup>	0.378

### Interpretation

Out of the total mass of input materials, PVC makes up 62%, followed by limestone of 16%, plasticiser makes up 14%, ESBO 3%, print film 2%, other additives make up the remaining of 3%. The bulk of the environmental impacts and primary energy demand are attributed to the manufacturing phase, covered by information modules A1-A3 of EN15804:2012+A2:2019.

As a result, PVC ranks first in terms of overall environmental impacts and is responsible for the greatest impact on all environmental impact indicators except GWP-bio, GWP-luluc, ODP, EP-freshwater, SQP, PERM, PERT, biogenic carbon content. ESBO and plasticiser rank second and third in terms of overall environmental impacts. Limestone has negligible impacts on all indicators.



## Summary, comments and additional information

### Front Cover Image



### About Amtico:

#### **LVT is in our DNA.**

Amtico is a British manufacturer of industry-leading flooring. A joint venture between American Biltrite and manufacturing giant Courtaulds, we began designing and making luxury vinyl tiles (LVT) in 1964. We're located in Coventry, a historic city, globally recognised for its continued contribution to British design, craft and engineering.

Today, we sell our floors in over 130 countries, but we are the only manufacturer who can proudly say we still make a large proportion of our LVT flooring from scratch, here in the UK.

#### **A passion for brilliance**

We've been setting the standard for creative expression in floor design for a long time. And we've become pretty good at it. The formula is simple. We combine relentless dedication with top-of-class expertise. Then we add that to every single floor we make. Our people stop at nothing to ensure every one of our products delivers what's required of it – excellence.

And if you need something completely unique, our in-house design team are ready to provide advice on product choice, laying patterns and finishes. Plus, we have a team of CAD experts who will work with you to draw up your design ready for manufacture.

### **Where we stand on sustainability**

When you choose an Amtico floor, we want you to be sure it's built on foundations that protect our planet and empower our people.

So, we are working on our strategy – a plan for tackling the major challenges, not in the next 20 years, but right now.

To read more about our strategy on sustainability, please visit <https://www.amtico.com/commercial/sustainability/>.

## **References**

BSI. Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products. BS EN 15804:2012+A2:2019. London, BSI, 2019.

BSI. Environmental labels and declarations – Type III Environmental declarations – Principles and procedures. BS EN ISO 14025:2010 (exactly identical to ISO 14025:2006). London, BSI, 2010.

BSI. Environmental management – Life cycle assessment – Principles and framework. BS EN ISO 14040:2006. London, BSI, 2006.

BSI. Environmental management – Life cycle assessment – requirements and guidelines. BS EN ISO 14044:2006. London, BSI, 2006.

BS EN ISO 10582:2018 Resilient floor coverings. Heterogeneous poly(vinyl chloride) floor covering. Specifications.

BS EN ISO 10874:2012+A1:2020 Resilient, textile and laminate floor coverings. Classification.

BS EN ISO 24340:2012 Resilient floor Coverings. Determination of thickness of layers

BS EN ISO 24346:2012 Resilient floor coverings. Determination of overall thickness.

BS EN ISO 23997:2012 Resilient floor coverings. Determination of mass per unit area.

BS EN 13501-1:2018 Fire classification of construction products and building elements. Classification using data from reaction to fire tests.

BS EN 13893:2002 Resilient, laminate and textile floor coverings. Measurement of dynamic coefficient of friction on dry floor surfaces.

BS EN 1815:2016 Resilient and laminate floor coverings. Assessment of static electrical propensity.

BS EN 12664:2001 Thermal performance of building materials and products. Determination of thermal resistance by means of guarded hot plate and heat flow meter methods. Dry and moist products of medium and low thermal resistance