



ANTI-SLIP



Nike World Headquarters - USA

THE HIGHEST STANDARDS FOR **SLIP RESISTANCE**

Bona Traffic HD Anti-slip



Bona Traffic HD Anti-slip

The highest standards for **slip resistance**

The world's toughest and fastest drying lacquer for wood floors exposed to extreme wear allowing full traffic to be resumed in just 12 hours.

Bona Traffic HD Anti-slip possesses all of the features of Bona Traffic HD but with the additional benefit of being formulated to meet the highest standards for slip resistance in commercial areas, staircases or other situations with an increased risk of spillage and slipping. Clear, non-yellowing lacquer perfected for wood floors.

APPLICATION

Designed to last, Bona Traffic HD ensures ultimate durability for extremely high-traffic areas.

- Heavy-traffic floors: airports, hotels, shopping malls etc.

KEY BENEFITS

- Lowers risk of accidental slips
- Ultimate speed and durability
- Allows full traffic after 12 hours
- Easy and safe to apply
- Very low odour
- GREENGUARD certified for low indoor emissions.
- Low solvent content (VOC), <5%.

TECHNICAL DATA

Type of varnish:	2-component waterborne polyurethane topcoat
Solids content:	32%
Sheen (at 60°):	15% (on glass)
Mixing ratio:	1 part Hardener to 1 litre Traffic HD Anti-slip or 0.41 L Hardener to 4,54 L Traffic HD Anti-slip (≈8 vol%).
Pot life:	max. 3 hours at 20°C (shorter if warmer).
Dilution:	If required, dilute with Bona Retarder (4%) for longer open time.
Drying time, until:	- Recoating: 2-3 hours* - Light use: 6 hours* - Possible to cover: 3 days*
	<i>*under normal climate conditions, 20°C/60% R.H.</i>
Application rate:	8-10 m ² /litre (100-120g/m ²) per coat
Safety:	Coating: Unclassified Hardener: Classified (see Safety Data Sheet)
Cleaning:	Wipe tools free from residual material before cleaning with a minimum of water. Dried material can be removed with acetone.
Shelf life:	Coating: 1 year from date of production in unopened original container. Hardener: 18 months from the date of production in unopened original container.
Storage/transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size:	3 x 4,95 litres incl. hardener (0,41 lit)