

Bona Mix Colour

CONCENTRATED PIGMENT PASTE

For custom tinting.



Concentrated pigment paste for use with Bona Nordic Tone or Bona Rich Tone.

Concentrated pigment paste for water soluble coatings. Specially suitable for tweaking the colour of Bona Nordic Tone and Bona Rich Tone but can also be added in small amounts to lacquers Bona Traffic/Traffic HD or Novia to give the floor a light tint. May also be added to Mix&Fill Plus to optimize the joint colour when joint filling.

- Intensifies colour effects
- Safe and easy application
- Combine with waterborne systems

Bona Mix Colour

CONCENTRATED PIGMENT PASTE

For custom tinting.

TECHNICAL DATA

Product type / base:	Concentrated pigment paste
Colours:	Black, Grey, White, Mahogany and Walnut.
Mixing ratio:	Maximum 250 ml for one 5 litre bottle (5%).
Fire risk:	No.
Safety:	Unclassified.
Cleaning:	Clean tools with water and soap. Dried material can be scrubbed away with soap and water
Shelf life:	5 years, from the date of production, in unopened original container.
Storage/Transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport. Store in a cool place.
Disposal:	Wastes and emptied containers should be handled in accordance with local regulations.
Pack size:	250 ml bottle.

Additional detailed information is noted in the appropriate Safety Data Sheet.

APPLICATION

Addition to Bona Nordic Tone or Bona Rich Tone:

1. Shake the pigment bottle and add to Bona Nordic or Rich Tone, max 5%.
2. Shake the mixture vigorously.

Note: After colouring, the surface should be sealed with an oil or hardwax oil.

Follow the instructions for Bona Nordic Tone or Bona Rich Tone for application.

Addition to Bona waterborne primers & lacquers.

1. Shake the pigment bottle and add the desired amount to the primer/lacquer. For a light tint, the dose is typically between 0,05% - 0,2%. Never exceed more than 5% pigment paste to the primer/lacquer. If mixing several cans, mix the entire quantity in one large container.
2. Shake the mixture vigorously.

Applying tinted primer or lacquer is challenging. Working with low concentrations of pigment and instead building

the desired colour intensity with multiple coats is advantageous in terms of colour evenness compared to trying to achieve a strong colour in a single application. Application marks or uneven colouration or gloss levels due to uneven application or inappropriate dosing are not accepted as a product claim. Uneven gloss levels may be rectified by the application of a further coat of lacquer with no mix colour added.

Addition to Bona Mix&Fill Plus

1. Mix Bona Mix&Fill Plus with wood dust per separate instruction.
2. Slowly and carefully add Mix Colour until a desired colouration is achieved. Note that the colour of the filler will not be the same when the filler has dried. Apply a thin coat of filler on a piece of cardboard or similar and evaluate the colour when dry prior to use on the floor.

Bona Mix Colour

CONCENTRATED PIGMENT PASTE

For custom tinting.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.