

Bona Retarder

PRIMER AND LACQUER ADDITIVE

Additive to slow drying & curing.



Additive that improves levelling and prolongs the open time of Bona waterborne finishes.

Bona Retarder should be used when the indoor humidity level is low and/or the temperature is high. It reduces the risk of the finish drying too quickly and of leaving roller marks in the dried coat.

- Facilitates application in warm/dry climates
- Prolongs open time
- Minimises the risk of overlap and discolouration

Bona Retarder

PRIMER AND LACQUER ADDITIVE

Additive to slow drying & curing.

TECHNICAL DATA

Mixing ratio:	Lacquers & primers: max 4%
Fire risk:	Non-flammable
Safety:	Unclassified.
Shelf life:	2 years from the date of production, in unopened original container.
Storage/Transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport. Store in a cool place.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size:	12 x 200 ml (120 boxes per pallet).

Additional detailed information is noted in the appropriate Safety Data Sheet.

APPLICATION

Add maximum 4% Bona Retarder to the lacquer or primer and shake or stir in thoroughly. (One 200 ml bottle to a 5 litre can of lacquer/primer = 4%).

Apply lacquer/primer mixed with Bona Retarder as normal according to the instructions on the respective product's technical data sheet.

IMPORTANT!

When using retarder with two component products, retarder must be added only **after** finish and hardener have been thoroughly mixed.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.